



LAFAYETTE

BASE SPECIFICATON FOR CORN PURCHASED

Grade	Moisture	TW	BCFM	Damage	Ht. Dmg
#2YC	15.0%	54.0	3.0%	5.0%	0.2%

Any load not meeting these specification will be subject to the following discounts:

<u>Factor</u>	<u>From</u>	<u>To</u>	<u>Discount</u>
Moisture	15.1% ABOVE	18.0% 18.0%	\$0.04 each 1/2% or part thereof Subject to Rejection
Test Weight	52.1 49.1 49.0 and below	54.0 52.0	\$0.01 each lb. or fraction thereof \$0.02 each lb. or fraction thereof Subject to Rejection
BCFM	3.1% 5.1% 6.1%	5.0% 6.0% ABOVE	\$0.03 each 1% or fraction thereof \$0.04 each 1% or fraction thereof Subject to Rejection
Damage	5.1% 7.1% 10.1%	7.0% 10.0% ABOVE	\$0.02 each 1% or fraction thereof \$0.03 each 1% or fraction thereof Subject to Rejection
Heat Damage	0.3%	2.0%	\$0.02 each 0.1%
Other	Sour, Musty, COFO, DLQ \$0.10 or Subject to Rejection depending on severity Heating or Hot \$0.10 or Subject to Rejection depending on severity Stone \$0.25 or Subject to Rejection MAXIMUM VOMITOXIN - 5 PPM		
Misc. Charges	\$4.50 will be charged per truck for grading		

Any truck determined to be loaded in such a way as to interfere with the taking of a representative sample (plugging) will be subject to rejection

DISCOUNT SCHEDULE SUBJECT TO CHANGE WITHOUT NOTICE