

LAFAYETTE

BASE SPECIFICATON FOR CORN PURCHASED

Grade	Moisture	ТW	BCFM	Damage	Ht. Dmg
#2YC	15.0%	54.0	3.0%	5.0%	0.2%

Any load not meeting these specification will be subject to the following discounts:

Factor	<u>From</u>	<u>To</u>	<u>Discount</u>			
Moisture	15.1%	18.0%	\$0.06 each 1/2% or part thereof			
	ABOVE	18.0%	Subject to Rejection			
Test Weight	52.1	54.0	\$0.01 each lb. or fraction thereof			
	49.1	52.0	\$0.02 each lb. or fraction thereof			
	49.0 and below		Subject to Rejection			
BCFM	3.1%	5.0%	\$0.03 each 1% or fraction thereof			
	5.1%	6.0%	\$0.04 each 1% or fraction thereof			
	6.1%	ABOVE	Subject to Rejection			
Damage	5.1%	7.0%	\$0.02 each 1% or fraction thereof			
	7.1%	10.0%	\$0.03 each 1% or fraction thereof			
	10.1%	ABOVE	Subject to Rejection			
Heat Damage	0.3%	2.0%	\$0.02 each 0.1%			
Other	Sour, Musty, COFO, DLQ \$0.10 or Subject to Rejection depending on severity Heating or Hot \$0.10 or Subject to Rejection depending on severity Stone					
Misc. Charges	\$0.25 or Subject to Rejection MAXIMUM VOMITOXIN - 5 PPM					

Any truck determined to be loaded in such a way as to interfere with the taking of a representative sample (plugging) will be subject to rejection

DISCOUNT SCHEDULE SUBJECT TO CHANGE WITHOUT NOTICE

Effective 9/28/22