



Loudon Spec

BASE SPECIFICATON FOR CORN PURCHASED

Grade	Moisture	TW	BCFM	Damage	Ht. Dmg
#2YC	15.5%	54	3%	5%	.3%

Any load not meeting these specifications will be subject to the following discounts:

FACTOR	FROM	TO	DISCOUNT/BU
MOISTURE	0.000	15.099	0.000
	15.100	15.599	0.000
	15.600	16.099	0.040
	16.100	16.599	0.080
	16.600	17.099	0.120
	17.100	17.599	0.160
	17.600	18.099	0.200
	18.100	18.599	0.240
	18% AND ABOVE SUBJECT TO REJECTION		
TEST WEIGHT	65.000	54.000	0.000
	53.999	53.000	0.010
	52.999	52.000	0.020
	51.999	51.000	0.040
	50.999	50.000	0.060
	49.999	49.000	0.080
	48.999	48.000	0.100
	47.999	47.000	0.120
	46.999	46.000	0.140
	45.999	45.000	0.160
52# AND BELOW SUBJECT TO REJECTION			
DAMAGE	0.000	5.099	0.000
	5.100	6.099	0.010
	6.100	7.099	0.020
	7.100	8.099	0.050
	8.100	9.099	0.080
	9.100	10.099	0.110
	10.100	11.099	0.150
	11.100	12.099	0.190
	12.100	13.099	0.230
5% AND ABOVE SUBJECT TO REJECTION			
FOREIGN MATERIAL	0.000	3.099	0.000
	3.100	4.099	0.030
	4.100	5.099	0.060
	5.100	6.099	0.100
	6.100	7.099	0.140
	7.100	8.099	0.190
	8.100	9.099	0.240
	9.100	10.099	0.290
3% AND ABOVE SUBJECT TO REJECTION			

- OTHER:** **Sour, Musty, COFO, DLGQ**
 \$0.10 or Subject to Rejection depending on severity
Heating or Hot
 \$0.10 or Subject to Rejection depending on severity
Stone
 \$0.10 or Subject to Rejection
Infested
 \$0.10 or Subject to Rejection

Discount Schedule Subject to Change without Notice

Effective 5/01/2025